

## Natural Light & with Flash

Not sure whether you need the flash? Natural Light & with Flash takes two photos in quick succession, one with flash and one without, eliminating the guesswork of flash photography.



Natural Light (flash off)

With Flash

## Tracking AF

Great for capturing dynamic close-ups, this function keeps fast moving subjects in the frame and in focus, even when the zoom is fully extended.



## AA Batteries

The FinePix S4200 can be powered by four AA-type alkaline batteries,\* affording a convenient source of power when you're on the road and eliminating the need to carry a bulky charger.



\*Included

## Date Stamp

Shooting date and time can be embedded in the lower right-hand corner of the image files.

## SPECIFICATIONS

Number of effective pixels <sup>*1</sup>	14.0 million pixels
Image sensor	1/2.3-inch CCD with primary color filter
Storage media	Internal memory (none), SD/SDHC/SDXC memory card <sup>*2</sup>
Lens	Fujinon 24x optical zoom lens f=4.3 - 103.2 mm, equivalent to 24 - 576 mm on a 35 mm camera F3.1 (Wide) - F5.9 (Telephoto) 11 groups 15 lenses
Digital zoom	Approx. 6.7x (up to approx. 160.8x, with 24x optical zoom)
Aperture	F3.1 / F8 (Wide), F5.9 / F8 / F20 (Telephoto) with ND filter
Focus distance (from lens surface)	Normal: (Wide) Approx. 40 cm to infinity / 1.3 ft. to infinity, (Telephoto) Approx. 2.8 m to infinity / 9.1 ft. to infinity Macro: (Wide) Approx. 7 cm - 3.0 m / 2.7 in. - 9.8 ft., (Telephoto) Approx. 2.0 m - 3.0 m / 6.5 ft. - 9.8 ft. Super Macro: Approx. 2 cm - 1.0 m / 0.8 in. - 3.2 ft.
Sensitivity	Auto, Equivalent to ISO 64/100/200/400/800/1600/3200*6400* (Standard Output Sensitivity) *ISO 3200/6400 is effective in image size S.
Image stabilizer	CCD shift type
Electronic viewfinder	0.2-inch, Approx. 200,000 dots, color LCD viewfinder, Approx. 97% coverage
LCD monitor	3.0-inch, Approx. 230,000 dots, TFT color LCD monitor, Approx. 97% coverage
Movie recording	1280 x 720 pixels, 640 x 480 pixels, 320 x 240 pixels (30 frames/sec.) with monoaural sound Optical zoom function can be used.
Power supply <sup>*3</sup>	4xAA type alkaline batteries (included) / 4xAA type Ni-MH rechargeable batteries (sold separately) / 4xAA type lithium batteries (sold separately)
Dimensions	118.0 (W) x 80.9 (H) x 99.8 (D) mm / 4.6 (W) x 3.1 (H) x 3.9 (D) in.
Weight	Approx. 543 g / 19.1 oz. (including battery and memory card)
Guide to the number of available frames for battery operation	Alkaline batteries: Approx. 300 frames (AUTO mode), Ni-MH rechargeable batteries: Approx. 500 frames (AUTO mode), Lithium batteries: Approx. 700 frames (AUTO mode)
Accessories included	4xAA type alkaline batteries, Shoulder strap, USB-A/V cable, Lens cap and Lens cap cord, CD-ROM, Owner's manual

\*1: Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

\*2: Please see the Fujifilm website to check memory card compatibility.

\*3: Manganese dry and nickel-cadmium batteries cannot be used with this product.



For more information, please visit our Website:  
[http://www.fujifilm.com/products/digital\\_cameras/index.html](http://www.fujifilm.com/products/digital_cameras/index.html)

Specifications and design are subject to change without notice.  
All sample photos are simulated images.



# 24x

FUJINON Optical Zoom  
24mm-576mm

14 Megapixels

Fujinon 24x Optical Zoom

3.0-inch LCD

HDMI  
High Definition Multimedia Interface

FULL HD  
PHOTO

HD  
MOVIE





# 24x FUJINON Optical Zoom

24mm-576mm

Featuring sturdy, dust-free sealed construction and the feel of a digital SLR, the FinePix S4200 is equipped with a powerful Fujinon 24x optical zoom lens, for versatile imaging performance ranging from wide-angle 24mm to an impressive 24x telephoto.



24mm Wide Angle



15x Optical zoom



24x Optical zoom



## 14 Megapixels

The powerful 14-megapixel CCD sensor produces high resolution photos and movies, perfect for enlarged prints or big-screen display.



## 3.0-inch LCD & Bright EVF


A spacious 3.0-inch LCD screen makes composing and viewing images a pleasure. And the bright, clear electronic viewfinder gives you additional flexibility in your shooting style.

## EVF Offers More Shooting Options

In addition to enhanced visibility in bright daylight, the bright EVF accommodates a traditional shooting style, making it easy to steady the camera, even when shooting with the 24x zoom fully extended.

## Dual Image Stabilization (Ⓜ)

Combining CCD-shift image stabilization with high sensitivity, the FinePix S4200 greatly reduces the effects of camera shake and subject blur, delivering crisp, clear shots across the entire zoom range.



Conventional digital camera



FinePix S4200

## SR AUTO SR AUTO with Red-Eye Removal (👁)

The FinePix S4200 automatically recognizes six of the most commonly photographed scenes and optimizes camera settings for beautiful results every time. And red-eye removal eliminates unsightly flash reflections to ensure flattering portraits and party pictures.

- Portrait
- Night
- Macro
- Landscape
- Night Portrait
- Backlit Portrait



Macro

## HD Movies

Captured in high-definition 16:9 format, both photos and movies can be displayed with stunning impact on your HDTV. The built-in mini HDMI port makes connection quick and easy.\*

\*Please use commercially available HDMI cable for HDTV connection.

